

AUTOTROL 363 VALVE

AUTOMATIC FILTER VALVE

COMPACT, LOW-PROFILE SOLUTION FOR A BROAD RANGE OF FILTRATION APPLICATIONS



FEATURES / BENEFITS

• Compact, low-profile design for easy installation in tight spaces.

• 3" NPT inlet and outlet ports for standard 1" and 1.5" pipe.

• 21" high, 12" wide, and 12" deep footprint.

• 3" NPT outlet port for standard 1" and 1.5" pipe.

• 12" high, 12" wide, and 12" deep footprint.

• 12" high, 12" wide, and 12" deep footprint.

• 12" high, 12" wide, and 12" deep footprint.

• 12" high, 12" wide, and 12" deep footprint.

OPTIONAL

• 12" high, 12" wide, and 12" deep footprint.

• 12" high, 12" wide, and 12" deep footprint.

• 12" high, 12" wide, and 12" deep footprint.

604-12" high, 12" wide, and 12" deep footprint.



12" high, 12" wide, and 12" deep footprint.



12" high, 12" wide, and 12" deep footprint.



12" high, 12" wide, and 12" deep footprint.



12" high, 12" wide, and 12" deep footprint.

ELECTRICAL

1. All wiring shall be in accordance with the National Electrical Code (NEC) and all applicable local codes.

GENERAL INFORMATION

1. The system shall be a 120/230V, 1-phase, 60Hz system.

2. The system shall be a 120V, 1-phase, 60Hz system.

3. The system shall be a 100V, 1-phase, 60Hz system.

4. The system shall be a 240V, 1-phase, 60Hz system.

5. The system shall be a 240V, 1-phase, 60Hz system.

6. The system shall be a 240V, 1-phase, 60Hz system.

7. The system shall be a 240V, 1-phase, 60Hz system.

GENERAL SPECIFICATION

1. The system shall be a 120/230V, 1-phase, 60Hz system.

2. The system shall be a 120V, 1-phase, 60Hz system.

3. The system shall be a 100V, 1-phase, 60Hz system.

4. The system shall be a 240V, 1-phase, 60Hz system.

5. The system shall be a 240V, 1-phase, 60Hz system.

6. The system shall be a 240V, 1-phase, 60Hz system.

7. The system shall be a 240V, 1-phase, 60Hz system.

8. The system shall be a 240V, 1-phase, 60Hz system.

9. The system shall be a 240V, 1-phase, 60Hz system.

10. The system shall be a 240V, 1-phase, 60Hz system.

PERFORMANCE

1. The system shall be a 120/230V, 1-phase, 60Hz system.

2. The system shall be a 120V, 1-phase, 60Hz system.

3. The system shall be a 100V, 1-phase, 60Hz system.

4. The system shall be a 240V, 1-phase, 60Hz system.

GENERAL CONNECTION

1. The system shall be a 120/230V, 1-phase, 60Hz system.

2. The system shall be a 120V, 1-phase, 60Hz system.

3. The system shall be a 100V, 1-phase, 60Hz system.

4. The system shall be a 240V, 1-phase, 60Hz system.

5. The system shall be a 240V, 1-phase, 60Hz system.

DIMENSION

1. The system shall be a 120/230V, 1-phase, 60Hz system.

2. The system shall be a 120V, 1-phase, 60Hz system.

3. The system shall be a 100V, 1-phase, 60Hz system.

4. The system shall be a 240V, 1-phase, 60Hz system.



FILTRATION & CO

1. The system shall be a 120/230V, 1-phase, 60Hz system.

2. The system shall be a 120V, 1-phase, 60Hz system.

3. The system shall be a 100V, 1-phase, 60Hz system.

4. The system shall be a 240V, 1-phase, 60Hz system.

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

4002833 REV B MR14 © 2014 Pentair Residential Filtration, LLC All Rights Reserved.